



IP503H Lite

IP TRANSCEIVER

You Can Talk and Listen at the Same Time Full-Duplex



Instant Wide Area Coverage Over an LTE/3G Network

It provides wide area communication using a cellular network.*

* Network coverage provided by a generally available data SIM card. Radio registration is required separately.

Multiple User Communication

Multiple users in the call groups can initiate calls instantaneously.

Priority Interrupt Calling

You can break into an on-going call to transmit an important message.

Industry Leading Compact and Lightweight Design

IP67 Dust-Tight and Waterproof

900 mW Powerful and Clear Audio

Other Features

- Individual, Talkgroup
- Built-in Bluetooth® capability and GPS

OPTIONAL ACCESSORIES

BATTERY PACK



BP-272
Rechargeable Li-ion
1880/2000 mAh(min./typ.)
IP67 waterproof

MULTI-CONNECTABLE
RAPID CHARGER

BC-202IP3L



BC-123S^{*1}
AC adapter for single unit



Connect up to 6 BC-202IP3L units



BC-228 AC adapter is required
for multiple connections.

^{*1} The straight plug type is required.

MULTI-CHARGER



BC-211^{*2}



BC-157S
AC adapter

^{*2} AC adapter may be supplied as standard,
depending on the version.

CHARGER CRADLE



BC-218
Charger cradle with
Bluetooth® function



BC-207S
AC adapter



HM-215
Speaker-microphone
for BC-218



MBA-7
Bracket adapter
for BC-218



MBF-1
Mounting base

SPEAKER-MICROPHONES



HM-183LS
IPX7 waterproof



HM-186LS

EARPHONE-MICROPHONES



HM-153LS



HM-166LS

HEADSETS



HS-102^{*3}
Earphone type



HS-94^{*4}
Earhook type



HS-95^{*4}
Behind-the-head type



HS-97^{*4}
Throat-microphone type



VS-3
Bluetooth® headset

^{*3} OPC-2359 is required when using HS-102.

^{*4} Either OPC-2006LS or OPC-2328 is required when using any of these headsets. (Simplex mode operation only.)

CARRYING CASE AND
SHOULDER STRAP

LC-185^{*5}



MB-57L
For use with LC-185

- **CP-22:** Cigarette lighter cable with DC-DC converter (12-24 V DC) (For use with BC-218)
- **CP-23L:** Cigarette lighter cable for 12 V DC (For use with BC-218)
- **CP-25H:** Cigarette lighter cable for 12 V DC (For use with BC-202IP3L single unit)
- **MB-135:** Belt clip. Same as supplied.
- **OPC-2006LS:** Plug adapter cable for VOX operation.
- **OPC-2328:** PTT switch cable
- **OPC-2359:** PTT switch cable

^{*5} Charging is possible while the case is attached.

SPECIFICATIONS

Network	EXP	LTE B1, B3, B7, B8, B20 W-CDMA B1, B8
	AUS	LTE B1, B3, B5, B7, B8, B28 W-CDMA B1, B5
Dimensions (W × H × D; Projections not included)	59 × 95 × 32 mm; 2.3 × 3.7 × 1.3 in (with BP-272)	
Weight (approx.)	240 g; 8.5 oz (with BP-272 and antenna)	
Voice Codec	G.726 (32 kbps)	
AF output power (8 Ω at 10% distortion)	Internal SP	More than 900 mW
	External SP	More than 200 mW
Operating time (TX : RX : standby = 5 : 5 : 90)	17 hours (with BP-272)	
Bluetooth®	Ver 2.1 +EDR	
GPS	Built-in	
Operating temperature	-10 °C to +60 °C; +14 °F to +140 °F	
IP rating	IP67 (dust-tight and waterproof) IP55/54 (dust and water jet / water resistance)	

^{*} Operating time may differ depending on operating environment.
All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications

MIL 810G Standard	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Supplied accessories

- BP-272 Li-ion battery pack
- MB-135 belt clip
- Hand strap
- Antenna

SPEAKERPHONE UNIT



VE-SP1

JUST SLOT IN THE IP503H **Lite** AND
START A VOICE CONFERENCE

- Portable operation with LR6 (AA)×8 cells
- Built-in loudspeaker and high sensitivity microphone
- Charges the radio while using with the AC adapter
- Great as a teleworking type solution

^{*} The transceiver is not supplied.

Note for IP503H users:

The IP503H **Lite** (front panel is blue) uses a generally available data SIM card and is controlled by the IP4000C system.
The IP503H **Lite** is not compatible with IP503H radios (black front panel) which use a closed network provided by custom Icom SIM card.



Please ask your Icom distributor in your country about the planned launch date of the service or other requirements. This product requires radio registration at Icom Inc.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries.

The Bluetooth® word mark and logos are registered trademark owned by Bluetooth SIG, Inc. and any use of such marks by Icom Inc. is under license. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icomjapan.com

Count on us!

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom Asia Co., Ltd.
www.icomasia.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Shanghai Icom Ltd.
www.bjicom.com

Icom France s.a.s.
www.icom-france.com